POLYREFLEX®

MULTI 7-33

TECHNICAL DATA SHEET




Dimensions:
15m² (1,25 x 12 m)

Weight: 395 g / m²

THERMAL RESISTANCE (R)*

Roofing	Walls and façades	Also applicable for
R = 3,18 m².K/W	**R = 2,22 m².K/W**	**ceilings and roofs**
2 cair cavities of 4	2 cair cavities of 2 cm	



TECHNICAL DATA

Emissivity: 0.07/0.09 (ETA/ETE 13-0525) (UNE-EN 16863:2024)
Reflectivity: 91% (UNE-EN ISO 22097:2023)
Core thermal resistance: 0.90 (ETA/ETE 13-0525) (UNE-EN 16863:2024)
Thermal resistance in roofs: 3.18 (with two 4 cm air chambers) (UNE-EN ISO 6946:2021)
Thermal resistance in ceilings: 2.04 (with an air chamber of 4 cm) (UNE-EN ISO 6946:2021)
Thermal resistance in walls: 2.22 (with two 2 cm air chambers) (UNE-EN ISO 6946:2021)
Aluminum purity: 98.5%
Includes radon barrier
Water vapor diffusion resistance: (ETA/ETE 13-0525) (UNE-EN ISO 22097:2023)
Fire classification: Class B-s1, d0 (within a system) / Euroclass F (EN 13501-1:2002) (Exposed)
Estimated service life: 25 years.

Important: Product installation must be carried out following the recommended characteristics. It is advised to seal joints and connections with metallized adhesive tape Polyfix. We are not responsible if the expected results are not achieved due to improper installation.

COMPOSITION

Reflective thermal insulation composed of two outer layers of protected aluminum, three inner polyester fiber layers, and two reflective PET aluminum films between the fiber layers.

Longitudinally heat-sealed, with no seams or intermediate welds.

APPLICATION

Walls and façades **(vertical installation on the interior or exterior).** Roofs and ceilings (**horizontal or inclined installation on the interior side).**

Internal partitions and divisions.
Suitable for any type of construction, whether new construction, renovation, aiming to use airtight cavities on both sides of the insulation.

Traditional construction systems, Steel Frame, wooden houses, modular or industrialized construction.



SOME OF THE ADVANTAGES

- Reduces heat flow through conduction.
- Longitudinal heat-sealed product to ensure airtightness of the air chambers and prevent the entry of humidity into the fibers, avoiding the spread of viruses, bacteria, and fungi.
- Protected exterior aluminum to guarantee low emissivity throughout the product's lifetime and maintain insulation performance.
- Easy and quick to install and use.

33 mm (+ air chambers)	84 mm	78 mm	80 mm	88 mm
POLYREFLEX MULTI 7-33	Expanded Polystyrene (EPS)	Extruded Polystyrene (XPS)	Mineral Wool	Glass Fiber

Optimer System
47 Plata Street, 28890 Loeches (Madrid), Spain Phone: (+34) 918 880 738
Mobile & WhatsApp: (+34) 663 668 071 | Email: comercial@optimersystem.com | **www.optimersystem.com**